

Other Fire Protection Products | Firefighting Nozzles for Fire Hose | [Master Stream Nozzles for use with Monitors](#)

Model 3A MN1

Product Description

Model 3A MN1. Constant gallonage type, 400, 500, 600, 700, and 800 gpm (1515, 1895, 2270, 2650, and 3030 Lpm), with a rated service pressure of 175 psi (12.1 bar). Available in stainless steel, aluminum and bronze materials, with a 3 in. (76 mm) water inlet connection. For use with model 3A WM1C and 3A WM2S monitor assemblies.

Details

Category	Master Stream Nozzles for use with Monitors
Class of Work	5511 - Water Spray Nozzles, FHose
Approval Standard	FM 5511 - Firefighting Nozzles for Use with Hose, Monitor Assemblies and other Firefighting Equipment
Certification Type	FM Approved
Listing Country	Turkiye

Company

3A Köpüklü Yangın Korunum

Sistemleri San. ve Tic. Ltd. Sti, Kultur Mahallesi, Efil Sokak No:2/414, Tatvan, Bitlis 13200, Turkiye



Member of the FM Global Group

Additional Info

Hydrants & Hoses

Nozzles

Master Stream Nozzles for use with Monitors

Inlet pressure and nozzle settings and the corresponding range and flow data is provided in the manufacturer's documentation.
