

Models 3A WM1C, 3A WM2S, 3A WM3C, 3A WM4B

Product Description

Model No	Construction Material	Rated Working Pressure		Inlet	Outlet	Optional Nozzles	Range of Motion
		psi	(bar)				
3A WM1C	Carbon Steel	175	(12)	3 inch, or 3 or 4 in. ANSI B16.5 Class 150 lb flange	3 in. nominal	3A MN1	H = 360° V= -45° to 90°
3A WM2S	Stainless Steel	175	(12)	3 inch, or 3 or 4 in. ANSI B16.5 Class 150 lb flange	3 in. nominal	3A MN1	H = 360° V= -45° to 90°
3A WM3C	Carbon Steel	175	(12)	4 inch, or 4 or 6 in. ANSI B16.5 Class 150 lb flange	4 in. nominal	3A MN2	H = 360° V= -45° to 90°
3A WM4B	Bronze	200	(13.7)	4 inch, or 4 or 6 in. ANSI B16.5 Class 150 lb flange	4 in. nominal	3A MN2	H = 360° V= -45° to 90°

Details

Category	Hydrants & Hoses, Monitors
Class of Work	1421 - Monitor Nozzles
Approval Standard	FM 1421 - Fire Protection Monitor Assemblies
Certification Type	FM Approved
Listing Country	Turkiye

Company

3A Köpüklü Yangın Korunum
Sistemleri San. ve Tic. Ltd. Sti, Kultur Mahallesi, Efil Sokak No:2/414, Tatvan, Bitlis 13200, Türkiye